VOICEWAY AUDIO ROUTER AX-8



DESCRIPTION

AX-8 is an audio automatic switching for ATC radio systems. Main purpose of AX-8 is an automatic supervise sitting between radios configured as main and standby pairs and also it can read an SNMP from radio to indicate a radio status on the web to be an alternative RCMS.

FEATURES

- Proprietary SNMP and EUROCAE MIB file support
- Balanced audio input and output
- Programmable alarm output

- Transmitter, Receiver or Transceiver of radio configurable
- Timer trigger for main and standby radio switching
- Manual radio switching via local button and web interface

- NTP Time synchronization
- Dual Ethernet connection
- Linux operating system

- Fanless passive cooling
- Embedded web server for monitor and configuration
- 1 x USB connection
- Power source connector 15-25 VDC

SPECIFICATION

VCS PTT Type	Dry contact and +/- 12 - 48 VDC
Radio PTT Type	TTL and dry contacts
VCS SQL	Dry contact and optocoupler
Radio SQL	Dry contact and TTL
AUX Output signal	8-Bit TTL
AUX Input signal	4-Bit optocoupler
Analog Radio and VCS interface	RJ45 600 Ohm
Analog line output	600 ohm
Analog line input	600 ohm
Ethernet Connection	1 x GbE, 1 x MbE
DC Connector	XLR female
Time Reference	Hardware clock, NTP
OS memory	32GB uSD card
Systems memory	8GB DDR3
Hardware platform	Zynq 7020
Operating systems	Petalinux
Mechanical dimension	1U rack

www.ifz.co.th



CONTACT US FOR MORE INFO

02-171-7857

บริษัท ไอแอฟแซด จำกัด

36/59 ถนนมอเตอร์เวย์ แขวงคลองสองต้นนุ่น ลาดกระบัง กรุงเทพ 10520

contact@ifz.co.th